















## Introduction

MECO - DIT 954-6R is 5KV Digital Insulation Testers with  $3\frac{1}{2}$  Digit (1999 Counts) Large Display and Backlight. This measures Insulation Resistance upto  $2006\Omega$ .

## **Features**

- 31/2 Digit (1999 Counts) Large LCD Display
- Range Selection & Single Person Push Button Operation
- LCD with Green Backlight
- Data Holding Function
- Display with Annunciators
- Auto Range (Insulation Test)
- Red LED Indicator for HV (High Voltage)

- Inbuilt Protection Circuit to prevent the harm of reverse Voltages.
- · Battery Operated with AC Adaptor
- As per IS10656-1983
- As per EMC Standard IEC 61326-1 Class B
- Over Voltage CAT III, 600V
- As per Safety Standard IEC/EN 61010-1 & 61010-31
- IP 44 Protection

## **Electrical Specifications**

Accuracy: ±(% reading + digits) at 23°C ±5°C; RH < 75%

| Specification         | Test voltage             | Range  | Accuracy         | Resolution       |
|-----------------------|--------------------------|--|------------------|------------------|
|                       | 100V / 250V / 500V DC    | $0.1 \text{M}\Omega$ to $200 \text{M}\Omega$ | ±(3%rdg+5 dgt.)  | 0.01MΩ to 0.01GΩ |
|                       |                          | 200M $\Omega$ to 10G $\Omega$                | ±(5%rdg+5 dgt.)  |                  |
| Insulation Resistance |                          | 10GΩ to 20GΩ                                 | ±(10%rdg+5 dgt.) |                  |
| modulation resistance | 1000V / 2500V / 5000V DC | $0.1 \text{M}\Omega$ to $200 \text{M}\Omega$ | ±(3%rdg+5 dgt.)  | 0.01MΩ to 0.1GΩ  |
|                       |                          | 200M $\Omega$ to 10G $\Omega$                | ±(5%rdg+5 dgt.)  |                  |
|                       |                          | $10G\Omega$ to $200G\Omega$                  | ±(10%rdg+5 dgt.) |                  |

## **General Specifications**

| Display               | 3½ Digit (1999 Counts) Large LCD Display with 29mm Digit Height  |  |  |
|-----------------------|--|--|--|
| Over-Range Indication | '1' is displayed   |  |  |
| Operating Temperature | 0°C to 40°C (RH ≤ 80%)   |  |  |
| Storage Temperature   | - 10°C to 50°C [RH ≤ 75%]  |  |  |
| Power                 | 12V (Eight x 1.5V "AA" Battery) with AC Adaptor  |  |  |
| Dimensions            | 190 x 155 x 75mm (approx.)   |  |  |
| Weight                | 900 gms including batteries (approx.)  |  |  |
| Standard Accessories  | Insulation Resistance Measurement Test Leads for High Voltage x 1 Set, AC Adaptor x 1 pc, 1.5V "AA" Batteries x 8 pcs, Heavy Duty Carry Bag x 1 pc, Instruction Manual x 1 no. |  |  |