# **VACUUM FURNACE**

# metrex An ISO 9001-2015 Certified Company

## **MODEL: MVF - 1000**

#### **TECHNICAL SPECIFICATIONS**

Furnace Structure : Double layers steel casing with fan cooling

Inner vacuum furnace chamber Size = 200 x 200 x 200mm (W x D x H)

Suitable to keep Alumina tray of size =  $150 \times 150 \times 50$ mm. Outer steel cylindrical chamber with vacuum & gas purging

attachment.

Temperature Control : Programmable PID Digital auto temp. control (1 prog. x 16 segments)

Over-heat protection and thermocouple broken protection.

Rate of Heating adjustable from 1 to 150C / min. Soak time can be set

as desired.

Control Accuracy : + / - 1°C

Temperature : Working Temperature : 1100°C

Thermocouple : K-Type

Gas Purging : Purging gas inlet and outlet facility. Gas inlet in the bottom of the wall

and gas outlet in the top of the opp. Wall (Diagonally opposite)

Power : 4 KW

Control Panel : Placed on the side or bottom of the furnace, with Temp. & Vacuum

Indicator, Gas flow meter, switches, indicating etc.

Vacuum Pump and Valve: Pumping rate: 200 lt. / min Vacuum Double stage pump

10-2 torr by mechanical pump (on pump head)

KF-25 adapter and stainless steel pipe are connected between pump

and tube flange with precision ball valve

#### **OPTIONAL:**

Gas flow meter 50 to 500 SCCM (gas to be specified)

# SALT BATH FURNACE

#### MODEL: MSB-1000

### TECHNICAL SPECIFICATIONS

Salt bath furnace for quenching up to 800°C

Bath Volume: Dia = 70cm, Depth = 70cm

Material of Crucible: SS 310, 8mm Thickness

Heating Element : Kanthal A1 Temp. Range : 150°C to 800°C

Temp. Control: ± 1°C Operation: 6 to 12 HRS

Temp. Control: PID Temp. Control with contactor / Relay etc.

Construction: Cylindrical in shape, having top opening, with manual cover closing.

Heating element are placed on the circumference and over the height.

Insulation by ceramic fiber blanket with outer mild steel casing.

Power: 65 KW

Supply: 415V, 3 phase AC supply

#### ACCESSORIES (at extra cost)

# MS steel Frame / Structure : Frame / Structure which has provisions for following purposes To lift 200 Kg weight sample by motorised wire rope and pulley arrangement.

To move the sample Horizontally as well as vertically

# MS angle Iron Table: To place the sample of 200kg weight.

Dimensions: Length = 900mm, Width = 600mm, Height = 600mm





